



Guard Bracket Install Instructions

www.tamermotocross.com
402-420-9557

- Step 1 Remove stock center mounting bolt from throttle side of plastic fork guard
- Step 2 Install the Tamer bracket and install OEM bolt and tighten. Make sure bracket is straight.
- Step 3 Mark the small hole onto the plastic fork guard.
- Step 4 Remove plastic guard from bike. Drill a 3/16" hole at mark.
- Step 5 Chamfer inside of hole with a 1/2" deburring bit or a 1/2" drill bit. If using drill bit, do it by hand.
- Step 6 Install Phillips head screw through plastic from inside and then apply blue Loc-tite to threads.
- Step 7 Install Guard Bracket onto screw and tighten.
- Step 8 Install plastic fork guard back onto forks. Apply Loc-tite to bolt that goes through bracket and into fork leg.

All Honda big bikes must use this bracket

Suggested for all KTM big bikes to strengthen the fork guard

TOOLS NEEDED: Drill, 3/16" drill bit, tools to remove fork guard, Phillips screwdriver, Loctite thread locker

Fork guard bracket will not work on the 2014 KTM Race Replica 450SX-F



Guard Bracket Install Instructions

www.tamermotocross.com
402-420-9557

- Step 1 Remove stock center mounting bolt from throttle side of plastic fork guard
- Step 2 Install the Tamer bracket and install OEM bolt and tighten. Make sure bracket is straight.
- Step 3 Mark the small hole onto the plastic fork guard.
- Step 4 Remove plastic guard from bike. Drill a 3/16" hole at mark.
- Step 5 Chamfer inside of hole with a 1/2" deburring bit or a 1/2" drill bit. If using drill bit, do it by hand.
- Step 6 Install Phillips head screw through plastic from inside and then apply blue Loc-tite to threads.
- Step 7 Install Guard Bracket onto screw and tighten.
- Step 8 Install plastic fork guard back onto forks. Apply Loc-tite to bolt that goes through bracket and into fork leg.

All Honda big bikes must use this bracket

Suggested for all KTM big bikes to strengthen the fork guard

TOOLS NEEDED: Drill, 3/16" drill bit, tools to remove fork guard, Phillips screwdriver, Loctite thread locker

Fork guard bracket will not work on the 2014 KTM Race Replica 450SX-F



Guard Bracket Install Instructions

www.tamermotocross.com
402-420-9557

- Step 1 Remove stock center mounting bolt from throttle side of plastic fork guard
- Step 2 Install the Tamer bracket and install OEM bolt and tighten. Make sure bracket is straight.
- Step 3 Mark the small hole onto the plastic fork guard.
- Step 4 Remove plastic guard from bike. Drill a 3/16" hole at mark.
- Step 5 Chamfer inside of hole with a 1/2" deburring bit or a 1/2" drill bit. If using drill bit, do it by hand.
- Step 6 Install Phillips head screw through plastic from inside and then apply blue Loc-tite to threads.
- Step 7 Install Guard Bracket onto screw and tighten.
- Step 8 Install plastic fork guard back onto forks. Apply Loc-tite to bolt that goes through bracket and into fork leg.

All Honda big bikes must use this bracket

Suggested for all KTM big bikes to strengthen the fork guard

TOOLS NEEDED: Drill, 3/16" drill bit, tools to remove fork guard, Phillips screwdriver, Loctite thread locker

Fork guard bracket will not work on the 2014 KTM Race Replica 450SX-F

